

AR 6-8-12 SM

	AR-6SM	AR-8SM	AR-12SM
Input kW	1,1	1,5	2,4
Advised Pool Volume (m3)	10~19	14~28	23~46
Output kW(A24 / W15-28)	5,5	7,6	12,5
COP A24 / W15-28)	5,2	5,2	5,2
EER (A35 / W28)	2,4	2,4	2,4
Hot Water Max temperature	45°C	45°C	45°C
Power	220-1Ph-50Hz	220-1Ph-50Hz	220-1Ph-50Hz
Refrigerant	R410a	R410a	R410a
Compressor	Rotary	Rotary	Rotary
Condenser	Titanium	Titanium	Titanium
Pump	Not included	Not included	Not included
Noise	48	48	56
Product Size (mm)	1005x305x620	1005x305x620	1115x425x715
Net Weight (Kg)	58	67	90
Casing Material	Coated steel	Coated steel	Coated steel
Fan type	Axial	Axial	Axial
Fan units	1	1	1
Water Flow Volume (m3/h)	2	3	4,5
Water Pressure Drop (kPa)		4	5
Water connection (mm)	40	50	50
Controller	LCD Panel	LCD Panel	LCD Panel
Air Temperature range	5 - 40°C	5 - 40°C	5 - 40°C

